



XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Material Safety Data Sheet

---

1. Product and Company Identification

---

Trade Name: Nickel Manganese Alloy  
Chemical Formula: NiMn  
Recommended Use: Scientific research and development

Manufacturer/Supplier: XI'AN FUNCTION MATERIAL GROUP CO., LTD  
Street: No. 69, Gazelle Valley, High-Tech Zone  
City: XI'AN  
State: Shannxi  
Zip Code: 710077  
Country: China  
Tel #: +86-29-88993870/+86-13519132051

---

2. Hazards Identification

---

Signal Word: Danger



Hazard Statements: H228: Flammable solid (powder)  
H317: May cause an allergic skin reaction  
H351: Suspected of causing cancer  
H372: Causes damage to the lung, the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Inhalative

Precautionary Statements: P210: Keep away from heat/sparks/flame. No smoking.  
P240: Ground/bond container and receiving equipment.  
P260: Do not breathe dust/fume/gas/mist/vapors/spray  
P280: Wear protective gloves/protective clothing/eye protection/face protection  
P363: Wash contaminated clothing before reuse  
P405: Store locked up  
P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

HMIS Health Ratings (0-4): Powder Pieces & larger

Health:	1	1
Flammability:	3	0
Physical:	1	0

---

### 3. Composition

---

Chemical Family: Alloy  
Additional Names: Manganese Nickel alloy

Nickel (Ni):  
Percentage: 0-100 wt%  
CAS #: 7440-02-0  
EC #: 231-111-4

Manganese (Mn):  
Percentage: 0-100 wt%  
CAS #: 7439-96-5  
EC #: 231-105-1

---

### 4. First Aid Procedures

---

General Treatment: Seek medical attention if symptoms persist.  
Special Treatment: None  
Important Symptoms: None

Inhalation: Remove victim to fresh air. Supply oxygen if breathing is difficult. Seek medical attention.  
Ingestion: Seek medical attention.  
Skin: Wash affected area with mild soap and water. Remove any contaminated clothing. Seek medical attention.  
Eyes: Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention.

---

### 5. Firefighting Measures

---

Flammability: Non-flammable, except as powder

Extinguishing Media: Do not use water or CO<sub>2</sub> – use sand, extinguishing powder.  
Spec. Fire Fighting Procedure: Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products.

---

### 6. Accidental Release Measures

---

If Material Is Released/Spilled: Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Keep unprotected personnel away. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust.

Environmental Precautions: Isolate runoff to prevent environmental pollution.

---

## 7. Handling and Storage

---

Handling Conditions:	Wash thoroughly after handling.
Storage Conditions:	Store in a cool dry place in a tightly sealed container. Protect against electrostatic charging. Store apart from materials and conditions listed in section 10.
Work/Hygienic Maintenance:	Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air.
Ventilation:	Provide sufficient ventilation to maintain concentration at or below threshold limit.

---

## 8. Exposure Controls and Personal Protection

---

Permissible Exposure Limits:	1 mg/m <sup>3</sup> as Ni, long-term value
Threshold Limit Value:	0.02 mg/m <sup>3</sup> as Mn, long-term value (respirable fraction) 0.1 mg/m <sup>3</sup> as Mn, long-term value (inhalable fraction)
Special Equipment:	None
Respiratory Protection:	Use a respirator with type P100 (USA) or P3 (EN143) cartridges as a backup to engineering controls. Risk assessment should be performed to determine if air-purifying respirators are appropriate. Only use equipment tested and approved under appropriate government standards.
Protective Gloves:	Nitrile rubber, NBR 0.11mm thick.
Penetration time of glove material:	480 minutes
Eye Protection:	Safety glasses or goggles
Body Protection:	Protective work clothing. Wear close-toed shoes and long sleeves/pants.

---

## 9. Physical and Chemical Characteristics

---

Color	Metallic grey
Form:	Powder, Granules, Pellets, Sputtering target, Custom parts
Odor:	N/A
Water Solubility:	N/A
Boiling Point:	N/A
Melting Point:	N/A
Flash Point:	N/A
Autoignition Temperature:	N/A
Density:	N/A
Molecular weight:	N/A

---

## 10. Reactivity

---

Stability:	Stable under recommended storage conditions
Reacts With:	Oxidizing agents
Incompatible Conditions:	Halogens
Hazardous Decomposition Products:	Metal oxide fume, Nickel oxides, Manganese oxides

---

## 11. Toxicological Information

---

### Potential Health Effects:

Eyes:	May cause irritation
Skin:	May cause irritation
Ingestion:	May cause irritation
Inhalation:	May cause irritation
Chronic:	Chronic exposure to nickel causes damage to the lung, the kidneys and the liver through prolonged or repeated exposure. Chronic exposure to manganese may cause impairment to the central nervous system. Symptoms include sluggishness, sleepiness, muscle weakness, and loss of facial muscle control, edema, emotional disturbances, spastic gait and falling. Chronic manganese poisoning may develop after as little as three months of heavy exposure but usually cases develop after one to three years of exposure.

Signs & Symptoms: N/A

Aggravated Medical Conditions: N/A

Median Lethal Dose: N/A

Carcinogen: This product contains a component that has been suspected to be carcinogenic based on its IARC, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies  
IARC: 1 - Group 1: Carcinogenic to humans (Nickel, powder [particle diameter < 1 mm]) 2B - Group 2B: Possibly carcinogenic to humans (Nickel, powder [particle diameter < 1 mm])  
NTP: Reasonably anticipated to be a human carcinogen (Nickel, powder [particle diameter < 1 mm])  
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

---

## 12. Ecological Information

---

Aquatic Toxicity:	Moderate
Persistent Bioaccumulation Toxicity:	N/A
Very Persistent, Very Bioaccumulative:	N/A
Notes:	Do not allow product to reach sewage or water courses.

---

## 13. Disposal Considerations

---

Dispose of in accordance with local, state, national, and international regulations.

---

## 14. Transportation Data

---

Hazardous: Hazardous as powder only.



Hazard Class:	4.1 Flammable solids
Packing Group:	II
UN Number:	UN3089
Proper Shipping Name:	Metal powders, flammable, n.o.s (Nickel Manganese alloy)

---

#### 15. Regulatory Information

---

Sec 302 Extremely Hazardous:	No
Sec 304 Reportable Quantities:	N/A
Sec 313 Toxic Chemicals:	Yes

---

#### 16. Other Information

---

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised: 09/15/2015

Funchmater