

XI'AN FUNCTION MATERIAL GROUP CO., LTD Material Safety Data Sheet Zinc Selenide

1. Product and Company Identification Trade Name: Zinc selenide Chemical Formula: ZnSe Manufacturer/Supplier: XI'AN FUNCTION MATERIAL GROUP CO., LTD No. 69, Gazelle Valley, High-Tech Zone Street: City: XI'AN State: Shaanxi 710077 Zip Code: Country: China Tel #: +86-29-88993870/+86-13519132051 2. Hazards Identification Signal Word: Danger Hazard Statements: H301+H331: Toxic if swahowed or if inhale H373: May cause damage to organs through central nervous system, the liver, and the digestive system through prolonged or repeated exposure. Route of exposure: Oral, inhalative. H410 Very toxic to aquatic life with long lasting effects P260 Do not breathe dust/fume/gas/mist/vapours/spray Precautionary Statements: P264 Wash skin thoroughly after handling P273: Avoid release to the environment P270: Do not eat, drink, or smoke when using this product. P309: IF exposed or you feel unwell: P310: Immediately call a POISON CENTER or doctor/physician P302+P352: IF ON SKIN: Wash with soap and water P391: Collect spillage P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up P501: Dispose of contents/container in accordance with local/regional/national/international regulations HMIS Health Ratings (0-4): 3 Health: Flammability: 0 0 Physical:

| 3. Composition | |
|---------------------------------------|--|
| Chemical Family: Additional Names: | Ceramic None |
| Zinc selenide (ZnSe): | |
| Percentage: | 100 wt% |
| CAS #: | 1315-09-9 |
| EC #: | 215-259-7 |
| | 4. First Aid Procedures |
| General Treatment: | Immediately remove any clothing soiled by the product. Remove breathing apparatus only after contaminated clothing has been completely removed. In case of irregular breathing or respiratory arrest provide artificial respiration. Seek medical attention if symptoms persist. |
| Special Treatment: | None |
| Important Symptoms: | None |
| Inhalation: | Remove victim to fresh air. Supply oxygen if breathing is difficult. Remove breathing apparatus only after contaminated clothing has been completely removed. Seek immediate medical attention. |
| Ingestion: | Do not induce vomit. Seek immediate medical attention. |
| Skin: | Wash affected area with mild soap and water. Remove any |
| Eyes: | contaminated clothing. Seek immediate medical attention. Flush eyes with water, blinking often for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek immediate medical attention. |
| | |
| | 5. Firefighting Measures |
| Flammability: | Non-flammable |
| Extinguishing Media: | No special restrictions – use suitable extinguishing agent for surrounding material and type of fire. |
| Spec. Fire Fighting Procedure: | Use full-face, self-contained breathing apparatus with full protective clothing to prevent contact with skin and eyes. See section 10 for decomposition products. |
| (| 6. Accidental Release Measures |
| If Material Is Released/Spilled: | Wear appropriate respiratory and protective equipment specified in special protection information. Isolate spill area and provide ventilation. Vacuum up spill using a high efficiency particulate absolute (HEPA) air filter and place in a closed container for disposal. Take care not to raise dust. |
| Environmental Precautions: | |
| Environmental Precautions: | Isolate runoff to prevent environmental pollution. |

| | 7. Handling and Storage |
|--|---|
| Handling Conditions: Storage Conditions: | Wash thoroughly after handling. Keep container tightly sealed. Store in a cool dry place in a tightly sealed container. Ensure good ventilation at the workplace. Open and handle container with care. Store apart from materials and conditions |
| Work/Hygienic Maintenance: | listed in section 10. Do not use tobacco or food in work area. Wash thoroughly before eating and smoking. Do not blow dust off clothing or skin with compressed air. |
| Ventilation: | Provide sufficient ventilation to maintain concentration at or below threshold limit. |
| 8. Expo | sure Controls and Personal Protection |
| Permissible Exposure Limits: Threshold Limit Value: | 0.2 mg/m ³ as Se, long-term value 0.2 mg/m ³ as Se, long-term value |
| Special Equipment: | None |
| Respiratory Protection: | Dust Respirator |
| Protective Gloves: | Rubber gloves |
| Eye Protection: | Safety glasses or goggles |
| Body Protection: | Protective work clothing. Wear close-toed shoes and long sleeves/pants. |
| | |
| 9. Ph | ysical and Chemical Characteristics |
| Color | Red |
| Form: | Powder, Granules, Pellets, Sputtering target, Custom parts |
| Odor: | Odorless |
| Water Solubility: | Insoluble |
| Boiling Point: | N/A >1100 °C |
| Melting Point: Flash Point: | >1100 C N/A |
| Autoignition Temperature: | N/A |
| Density: | 5.42 g/cc |
| Molecular weight: | 144.33 g/mol |
| | 10. Reactivity |
| Stability: | Stable under recommended storage conditions |
| Reacts With: | Bases, Oxidizing agents |
| Incompatible Conditions: | None |
| Hazardous Decomposition Products: | Hydrogen selenide, Selenium dioxide, Metal oxide fume |
| | 11. Toxicological Information |
| Potential Health Effects: | |
| Eyes: | May cause irritation |
| Skin: | May cause irritation |
| Ingestion: | Toxic |
| Inhalation: Chronic: | Toxic Selenium may cause amyotropic lateral sclerosis, bronchial irritation, gastrointestinal distress, vasopharyngeal irritation, garlic odor on breath and sweat, metallic taste, pallor, irritability, excessive fatigue, loss of fingernails and hair, pulmonary edema, anemia and weight loss. Zinc containing fumes may cause metal fume fever. Effects include dry throat, metallic taste, chest pain, dyspnea, rales, and dry cough. Several hours later, chills may occur with lassitude, malaise, fatigue, headache, |

back pain, Muscle cramps, blurred vision, nausea, fever, perspiration, vomiting and leukocytosis.

| Signs & Symptoms: Aggravated Medical Conditions: | N/A N/A |
|--|---|
| Median Lethal Dose: | N/A |
| Carcinogen: | N/A |
| | 12. Ecological Information |
| Aquatic Toxicity: Persistent Bioaccumulation Toxicity: Very Persistent, Very Bioaccumulative Notes: | High No further relevant information available. e: No further relevant information available. Very Toxic to aquatic life. May cause long lasting harmful effect on aquatic life. Do not allow material to be released to the environment without proper governmental permits. Do not allow product to reach any water sources. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Do not allow undiluted product or large quantities to reach ground water, water course or sewage system. Avoid transfer into the environment. |
| | 13. Disposal Considerations |
| Dispose of in accordance with local, sta | te, national, and international regulations. 14. Transportation Data |
| Hazardous: | Hazardous for transportation. |
| Hazard Class: Packing Group: UN Number: Proper Shipping Name: | 6.1 Toxic substances III UN3283 Selenium compound, solid, n.o.s. (Zinc selenide) |
| | 15. Regulatory Information |
| Sec 302 Extremely Hazardous: Sec 304 Reportable Quantities: Sec 313 Toxic Chemicals: | No N/A Yes |

16. Other Information

This safety data sheet should be used in conjunction with technical sheets. It does not replace them. The information given is based on our knowledge of this product, at the time of publication. It is given in good faith. The attention of the user is drawn to the possible risks incurred by using the product for any other purpose other than that for which it was intended. This does not in any way excuse the user from knowing and applying all the regulations governing his activity. It is the sole responsibility of the user to take all precautions required in handling the product. The aim of the mandatory regulations mentioned is to help the user to fulfill his obligations regarding the use of hazardous products.

Document Last Revised:

08/21/2017

EUNATER